



ProFast



**Standstill in any
process costs money!**





“ProFast; fast floor and wall finishes that respect the environment”

Prokol launches a new coating technology based on polyurea under the name of ProFast.

This unique range of products exceeds all expectations!

In the market, Prokol is known as a specialist in the field of polyurea hot spray coatings. New developments have enabled Prokol to launch a new range of products with sublime properties. This well-balanced programme offers a host of benefits for both applicator and clients.

The advantages of ProFast

- Chemical resistance.
- Up to 3 times more wear and scratch-resistant than epoxy and polyurethane coatings, so suitable for a wide range of applications.
- Good adhesive properties on a wide range of surfaces.
- Capable of carrying mechanical loads after 2 to 3 hours.
- Available in 15 standard colours. Other colours are available on a project basis and on request.
- Performs well under both high and low temperatures.
- Entirely solvent-free, giving it a “green” character.
- Entirely water-tight and easy to clean.
- Colour-fast, UV-proof with excellent preservation of colour and gloss.
- Possibilities to achieve smooth, anti-skid and decorative floors in combination with colour flakes or coloured quartz.

“Our manually processable ProFast products have special properties that leave traditional products far behind”

Got no time to repair the floor?

The progress of an operating process is often a hotly debated subject. There is little to no time to repair or renovate a floor, let alone to allow the products to harden sufficiently.

“Time is money. Our ProFast products ensure that process downtime is kept to a minimum. Your floor can carry mechanical loads again after approximately 2 hours”



This means that your floor can be repaired easily in most cases. With the ProFast products you don't have to worry about anything, and they reduce "risks" to a minimum.

The ProFast advantages for the applicator

The ProFast product range comprises various primers, floor and wall coatings, mortar and trowel products and transparent sealants. Whether you want to roll, repair, trowel or apply mortar; ProFast makes it possible.

ProFast:

- Is moisture-tolerant up to 10%.
- The product can be applied at very low temperatures. It can be applied at temperatures well below zero degrees centigrade.
- Is as quick as PMMA and polyester products, but without the strong smells.
- Is entirely solvent-free.
- Is step-proof and paintable after 1 to 2 hours.
- Can be mechanically loaded after 2 to 3 hours and chemically loaded after 2 days.

Where can you use ProFast products?

ProFast products are extremely versatile and can be applied on balconies, in access galleries, stairwells, underground car parks, production areas and distribution centres. Each project is specific, please consult the technical data sheets and technical representative for further advice.

"Applying multiple layers within one day poses no problem at all. The speed of ProFast ensures that completion time of your projects can be expedited. ProFast saves both you and your client time, money, it saves the environment and it reduces production down-time."

In other words, anywhere where speed and accessibility are vital, in combination with the highest possible quality.

Total solutions in polymer technology

Your supplier:



T +31(0)492 547 665 • F +31(0)492 547 592
www.prokol.nl • info@prokol.nl